


JHS-32S-C-XXX (C键位)








JHS-32S-A-XXX (A键位)



JHS-32S-B-XXX (B键位)



JHS-32S-C-XXX (C键位)



1. 工作温度:-40℃~125℃
2. 额定电压:60V DC
3. 额定电流:电源:13A MAX, 信号:5A MAX
4. 耐 电 压:3000V DC
5. 防护等级:IP67/IP6K9K
6. 机械寿命:100 Min.
7. 符合RoHS标准

JHS-32S-X

母头

S-signal
JHS信号
产品系列

键位
A
B
C

更改内容描述	版本	签名	日期	批准
首发	V1.0	<i>Lai</i>	2024.02.27	

成品编号	零件描述	数量	电缆规格
JHS-32S-A-XXX JHS-32S-B-XXX JHS-32S-C-XXX	1. 0母端子JHS32-S10-1822	26	18-22AWG
	1. 6母端子JHS32-S16-1418	6	14-18AWG
	防尘盖JHS32-S-CAP	1	
	1. 6密封塞JHS32-SEAL-16	26	
	3. 0密封塞JHS32-SEAL-30	6	
	连接器组件	1	

						 君灏新能源 JONHAO			
设计	Lai	2024.01.20					名称	32芯低压信号连接器(孔)	
审核	Zhao	2024.01.20					型号	JHS-32S-X	
工艺	Duan	2024.01.20					视图	尺寸	角度
批准	Zhou	2024.01.20					$.X \pm 0.5$ $.XX \pm 0.30$ $.XXX \pm 0.15$	$.X' \pm 3'$ $.XX' \pm 2'$ $.XXX' \pm 1'$	
标准化	Wang	2024.01.20					客户图纸	重量:	比例1:1 共1张第1